

MATERIAL SAFETY DATA SHEET

SECTION I PREPARATION AND PRODUCT INFORMATION

MANUFACTURER: THE POTTERY SUPPLY HOUSE LTD.
ADDRESS: 1120 SPEERS ROAD
OAKVILLE, ONTARIO L6L 2X4
SUPPLIER: THE POTTERY SUPPLY HOUSE LTD. TEL: 1 800 465-8544
ADDRESS: 1120 SPEERS ROAD 905 849-5540
OAKVILLE, ONTARIO L6L 3X4 FAX: 905 849-0001
MATERIAL NAME: **CONE 6 LEADLESS GLAZE: PUMPERNICKEL**
MATERIAL USE: WATER-BASED STONEWARE GLAZE

SECTION II HAZARDOUS INGREDIENTS

INGREDIENT	%	C.A.S.#	LD50	LC50
FRIT,* CONTAINING FUSED COMPOUNDS OF:	30 - 60	65997-18-4	N.A.	N.A.
ALUMINUM	1 - 5	1344-28-1	N.A.	N.A.
CALCIUM	3 - 7	1305-78-8	N.A.	N.A.
SILICON	10 - 30	67762-90-7	N.A.	N.A.
SODIUM	1 - 5	12401-86-4	N.A.	N.A.
BORON	3 - 7	1303-86-2	N.A.	N.A.
SILICA, QUARTZ	3.0 -7.0	14808-96-6	N.A.	N.A.
BLUE STAIN* CONTAINING OXIDES OF:	0.1 - 1.0	68187-40-6	N.A.	N.A.
SILICON	0.1 - 1.0	14808-60-7	N.A.	N.A.
COBALT	0.1 - 1.0	1396-06-1	N.A.	N.A.
NICKEL OXIDE	0.5 - 1.5	1313-99-1	>5000 mg/kg (ORAL, RAT)	N.A.

*A FUSED SILICATE COMPOUND CONTAINING REPORTABLE OXIDES. FORMED BY HIGH TEMPERATURE FUSION OR CALCINATION, IT MAY NOT EXHIBIT ANY OF THE PROPERTIES OF THE METAL COMPOUNDS LISTED.

SECTION III PHYSICAL DATA

PHYSICAL STATE: LIQUID/SOLID SUSPENSION.
ODOUR / APPEARANCE: OPAQUE, LIGHT GREY FLUID WITH MILD ODOUR.
ODOUR THRESHOLD: NOT AVAILABLE
SPECIFIC GRAVITY: APPROXIMATELY 1.6
VAPOUR PRESSURE: NOT AVAILABLE
VAPOUR DENSITY: NOT AVAILABLE
EVAPORATION RATE: NOT AVAILABLE
BOILING POINT: NOT AVAILABLE
FREEZING POINT: APPROXIMATELY 0° C (WATER)
PH: NOT AVAILABLE
COEFF. WATER/OIL
DISTRIBUTION: NOT AVAILABLE

SECTION IV FIRE OR EXPLOSION HAZARD

CONDITIONS OF FLAMMABILITY: NOT FLAMMABLE
MEANS OF EXTINCTION: NOT APPLICABLE
FLASHPOINT, METHOD OF DETERMINATION: NOT APPLICABLE
UPPER FLAMMABLE LIMIT: NOT APPLICABLE
LOWER FLAMMABLE LIMIT: NOT APPLICABLE
AUTO-IGNITION TEMPERATURE: NOT APPLICABLE
HAZARDOUS COMBUSTION PRODUCTS: TOXIC METAL FUMES MAY BE EVOLVED IN A FIRE. VERY SMALL QUANTITIES (<1%, TOTAL) OF CARBON DIOXIDE, CARBON MONOXIDE, HYDROCHLORIC ACID, FORMALDEHYDE, AND NO_x/SO_x VAPOURS MAY BE LIBERATED IN A FIRE.
EXPLOSION DATA,
SENSITIVITY TO MECHANICAL IMPACT: NONE
SENSITIVITY TO STATIC DISCHARGE: NONE

SECTION V REACTIVITY DATA

CONDITIONS UNDER WHICH PRODUCT IS CHEMICALLY UNSTABLE: ACIDIC
NAME OF INCOMPATIBLE SUBSTANCES: POWERFUL ACIDS, BASES AND OXIDIZING AGENTS.
CONDITIONS OF REACTIVITY: NONE KNOWN
HAZARDOUS DECOMPOSITION PRODUCTS: TOXIC FUMES MAY BE RELEASED DURING FIRING

SECTION VI TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY: SKIN CONTACT: POSSIBLE IRRITANT. REFER TO EFFECTS OF ACUTE AND CHRONIC EXPOSURE.
SKIN ABSORPTION: UNLIKELY
EYE CONTACT: POSSIBLE IRRITANT.
INHALATION: IRRITATING TO THE RESPIRATORY TRACT.
INGESTION: THIS PRODUCT IS LOW IN ACUTE TOXICITY.

EFFECTS OF ACUTE EXPOSURE: CONTACT WITH EYES, SKIN AND RESPIRATORY TRACT MAY CAUSE PHYSICAL IRRITATION AND INFLAMMATION. COBALT AND NICKEL COMPOUNDS HAVE BEEN SHOWN TO CAUSE DERMATITIS AND SENSITIZATION IN SENSITIVE INDIVIDUALS. OVEREXPOSURE TO RESPIRABLE DUST OR MIST MAY CAUSE SKIN, EYE AND RESPIRATORY IRRITATION DUE TO THE PHYSICAL NATURE OF THE PARTICULATES. REPEATED AND PROLONGED BREATHING OF THESE PARTICULATES MAY CAUSE COUGHING, WHEEZING IMPAIRED LUNG FUNCTION AND INCREASED SPUTUM PRODUCTION. SMOKING AGGRAVATES THESE EFFECTS. OVEREXPOSURE TO RESPIRABLE CRYSTALLINE SILICA DUST MAY CAUSE:
1/ SILICOSIS, A FORM OF PROGRESSIVE PULMONARY FIBROSIS.
2/ SCLERODERMA, AN IMMUNE SYSTEM DISORDER MANIFESTED BY A FIBROSIS OF THE LUNGS, SKIN AND OTHER INTERNAL ORGANS.
SILICOSIS INCREASES THE RISK OF TUBERCULOSIS.
RECENT EVIDENCE SUGGESTS AN ASSOCIATION BETWEEN RESPIRABLE EXPOSURE AND A HIGHER INCIDENCE OF KIDNEY LESIONS.
CRYSTALLINE SILICA INHALED FROM OCCUPATIONAL SOURCES IS CLASSIFIED (IARC) AS CARCINOGENIC TO HUMANS.
IARC HAS CONCLUDED THAT THERE IS SUFFICIENT EVIDENCE THAT NICKEL COMPOUNDS ARE CARCINOGENIC TO HUMANS (INHALATION). WORKERS WHO HAVE BEEN PRIMARILY EXPOSED TO NICKEL OXIDE SHOWED SOME EVIDENCE OF INCREASED LUNG CANCER. NICKEL OXIDE MAY BE A SINONASAL CANCER HAZARD.

EFFECTS OF CHRONIC EXPOSURE:

EXPOSURE LIMITS - TIME WEIGHTED
AVERAGE EXPOSURE VALUES (TWA EV):

GLAZE FRIT:	NOT ESTABLISHED	AS COMPONENT OXIDES:	CALCIUM	2.0 mg./m³	
			ALUMINUM	10.0 mg./m³	
			BORON	10.0 mg./m³	
			FUSED SILICON	0.1 mg./m³	
			SODIUM	N.A.	
	SILICA:	0.1 mg./m³			
	BLUE STAIN:	NOT ESTABLISHED	AS COMPONENT OXIDES:	SILICON	0.1 mg./m³
				COBALT (AS METAL)	0.02 mg./m³
	NICKEL OXIDE (AS Ni):	0.2 mg./m³			

IRRITANCY OF PRODUCT: REFER TO ROUTE OF ENTRY
SENSITIZATION OF PRODUCT: INHALATION OF SOME NICKEL AND COBALT COMPOUNDS MAY CAUSE AN IRRITATION OF RESPIRATORY ORGANS OF SENSITIVE PERSONS LEADING TO OBSTRUCTION OF AIRWAYS.
CARCINOGENICITY OF PRODUCT: REFER TO CHRONIC EFFECTS. COBALT IS CLASSIFIED (IARC) AS AN ANIMAL CARCINOGEN AND A POSSIBLE HUMAN CARCINOGEN. NICKEL
TERATOGENICITY OF PRODUCT: NO KNOWN EFFECTS
MUTAGENICITY OF PRODUCT: NO KNOWN EFFECTS
SYNERGISTIC MATERIALS: NONE KNOWN

SECTION VII PREVENTATIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT TO BE USED: THIS PRODUCT HAS BEEN SPECIFICALLY FORMULATED FOR BRUSH APPLICATION. USERS WHO APPLY BY SPRAYING ARE ADVISED TO WEAR SAFETY GLASSES AND AN APPROPRIATE RESPIRATOR (REFER TO EXPOSURE LIMITS). USERS WHO APPLY BY DIPPING ARE ADVISED TO WEAR RUBBER GLOVES TO PREVENT SKIN IRRITATION OR ALLERGIC REACTION.

ENGINEERING CONTROLS TO BE USED: NONE FOR BRUSH APPLICATION. THE USE OF VENTILATING EQUIPMENT IS RECOMMENDED FOR SPRAY APPLICATION. THIS PRODUCT CONTAINS CELLULOSE GUM (<1%) AND A PRESERVATIVE (<0.07%). ABOVE 227°C, CARBON MONOXIDE, CARBON DIOXIDE AND SMOKE ARE RELEASED AS THE GUM IS BURNT OFF. HYDROCHLORIC ACID, FORMALDEHYDE, SO_x AND NO_x VAPOURS MAY BE LIBERATED WHEN THE PRESERVATIVE IS FIRED OUT. AT HIGH TEMPERATURES, METAL FUMES MAY BE LIBERATED. **WHEN FIRING, USE A DOWNDRAFT OR OVERHEAD HOOD-TYPE EXHAUST.**

SECTION VII PREVENTATIVE MEASURES, CONTINUED

PROCEDURES TO BE FOLLOWED IN CASE OF SPILL: CLEAN UP WITH SPONGE OR SPATULA. CAUTION: SPILLS ARE SLIPPERY.
WASTE DISPOSAL: IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL LAWS. DO NOT EMPTY INTO WATER COURSES.

HANDLING PROCEDURES: AVOID GENERATING MIST OR DUST. MAINTAIN GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK OR SMOKE. WASH AFTER USE.

STORAGE REQUIREMENTS: DO NOT STORE NEAR FOODSTUFFS.

SPECIAL SHIPPING INFORMATION: NONE

SECTION VIII FIRST AID MEASURES

EYE EXPOSURE: FLUSH THOROUGHLY WITH WATER. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS.

SKIN EXPOSURE: WASH THOROUGHLY AND APPLY MOISTURIZING HAND CREAM TO DRIED, REDDENED SKIN. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

INGESTION: GIVE WATER. DON'T INDUCE VOMITING. SEEK MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION AS REQUIRED.

SECTION IX PREPARATION INFORMATION

MSDS PREPARED BY: JON WALLS
PREPARATION DATE: JANUARY 29, 2010

ALTHOUGH REASONABLE CARE HAS BEEN TAKEN IN THE PREPARATION OF THE INFORMATION CONTAINED HEREIN, THE POTTERY SUPPLY HOUSE EXTENDS NO WARRANTIES, MAKES NO REPRESENTATION AND ASSUMES NO RESPONSIBILITY AS TO THE ACCURACY OR SUITABILITY OF SUCH INFORMATION FOR APPLICATION TO PURCHASER'S INTENDED PURPOSES OR FOR CONSEQUENCES OF ITS USE.
